



Product Information

Mod.R&S 06 | Rev.4 | Update 08/2019 | Page 1



COLORPRINT®

Description PVC heat seal material with polyester backing, created for inkjet digital printing & cutting systems with solvent, eco solvent or HP Latex inks. The material grants a high covering power on dark fabrics. **Product containing phthalates. Not suitable for the production of toys or any other article specifically addressed to childcare.**

Suitable for cotton, polyester, performance wear, poly/cotton blends and spandex, not treated or dye sublimated

- Usage**
- Print and cut the material
 - Let the print dry **at least 12 hours** before rolling up, overlaying or heat transferring the material
- When printing on HP Latex plotter, set the drying temperature at 90°C*
- Weed the exceeding material
 - Remove the print from the polyester backing using Siser's TTD (adhesive, transparent and resistant to high temperatures)
 - Heat apply at the conditions shown on the right
 - Remove the application tape warm (in case of other application tapes, follow the specific instructions)

Washing Wait at least **24 hours** from application before washing. Washing resistance up to **60°C**, best inside-out. Do not use bleach or other aggressive chemical agents. Not suitable for dry cleaning. Not suitable for tumble dryer.

The product is REACH compliant
The product is certified for print with HP Latex inks

Certified for
HP Latex Inks

N.B. All information here contained are based on our experience. We recommend to perform a test before starting standard production. For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C




Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9105027958





The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation n. 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance).

This document can be subject to variations. Updated versions are available on our website www.siser.com

For further information, please contact our Sales Office.

 **Average thickness**
170 microns

 **Suggested cutting settings**
Blade: 45°
Pressure: 70 gf
Speed: 20 cm/sec

 **Transfer settings**
15 seconds at 150°C (300°F)
medium pressure (3-4 bar)

Washing temperature



Dry cleaning



Tumble dryer



Siser s.r.l.
Viale della Tecnica, 18
36100 Vicenza - Italy

Tel. +39 0444.287960
Fax +39 0444.287959
info@siser.it - www.siser.com

r.e.a. vi 171856
reg. imp. vi n° 14971
c.s. € 103.300 i.v.
p.iva 01591490246