



Product Information

Mod.R&S 06 | Rev.4 | Update 07/2019 | Page 1



STRIPFLOCK PRO

Description Plotter cut flock material with brilliant colours, suitable for cotton, polyester, poly/cotton blends (not suitable for dye sublimated fabrics). Adhesive polyester carrier.



Average thickness
500 microns

Usage

- Mirror cut
- Weed excess material
- Place it on the garment with its polyester carrier
- Heat apply at the conditions shown on the right
- Remove the carrier warm



Suggested cutting settings

blade 60°
pressure 80 gf
speed 15 cm/sec



Transfer settings

15 seconds at 155°C
(311°F)
medium pressure
(3-4 bar)

Washing

Wait at least **24 hours** from application before washing.
Washing resistance up to **60°C**, best inside-out.
Do not use bleach or other aggressive chemical agents.
Do not dry clean.
Suitable for tumble dry, cotton cycle

Washing temperature



Dry cleaning



Tumble dryer



The product is REACH compliant
The product is certified Öko-Tex® Standard 100 Class I



N.B. All information here contained are based on our experience.
We recommend to perform a test before starting standard production.
For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C



Management System
ISO 9001:2015



www.tuv.com
ID 9105027958

The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation n. 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance).

This document can be subject to variations.

Updated versions are available on our website www.siser.com

For further information, please contact our Sales Office.

Thank you



Siser s.r.l.
Viale della Tecnica, 18
36100 Vicenza - Italy

Tel. +39 0444.287960
Fax +39 0444.287959
info@siser.it - www.siser.com

r.e.a. vi 171856
reg. imp. vi n° 14971
c.s. € 103.300 i.v.
p.iva 01591490246