

PRODUCT INFORMATION

Mod. R&S.	Rev.	Last updated	Page
05	03	02/2016	1 of 1

T.T.D.

Description

Adhesive Polyester Film for the correct application of digital printing materials . It is available in three different grades of adhesion : ADVANCED, EASY and EVOLUTION

The adhesive side of the material is protected with **silicon paper**.

Medium thickness: 75 micron.

Range of application

PRODOTTO	TTD ADVANCED (low tack)	TTD EASY (medium tack)	TTD EVOLUTION (high tack)
COLORPRINT			
COLORPRINT EXTRA			
COLORPRINT NEW M			
COLORPRINT PU / MATT			
COLORPRINT PU EXTRA / MATT			
DIGITAL PERFOR			
EVOLUTION PRINT PLUS			
GLITTERPRINT		•	
SOFT PRINT COLOR VIVID / MATT			
SUBLITHIN MATT LT			

Procedure

Remove the protective paper from T.T.D.

Apply the T.T.D. onto the printed logo, manually or using a laminator, avoiding air

bubbles

Remove the backing of the digital, printed media

Heat apply following the instructions of the digital media

Remove T.T.D. Advanced according the given instructions for the product in use..

Certifications

The product is REACH approved



Siser s.r.l.

Viale della Tecnica n° 18 36100 Vicenza - Italy Tel. +39 0444.287960 Fax +39 0444.287959 info@siser.it - www.siser.it N.B. All information given in this sheet are based on our experience.
We always recommend performing a test before starting standard production.
For best results we recommend to store the product away from direct sunlight.

The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation n. 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance). This document can be subject to variations. Updated versions are available on our website www.siser.it. For further information, please contact our Sales Office. Thank you.