



# EASY PUFF®

## SPECIFICATIONS

Composition	Average Thickness	Carrier	Certifications
PU	145 microns	adhesive polyester	REACH n° 1907/2006/EU  

## APPLICATION INSTRUCTIONS

APPLIES ON	SUGGESTED CUTTING SETTINGS			TRANSFER SETTINGS			
cotton, polyester, poly/cotton blends  not treated with silicon or died with sublimation inks	Blade	Pressure	Speed	Time	Temperature	Pressure	Peel
	45°	70 gf	25 cm/sec	10-12 sec	135-140°C	medium	hot

- Cut mirrored and peel off excess material
- Place the decoration on the fabric
- Apply following the recommended parameters with a heat press (not with a home iron)
- Remove the carrier while hot

### PRODUCT HIGHLIGHTS

- Easy to cut and weed, thanks to the sticky carrier
- 3D-effect

! Even when using the recommended parameters, due to the different chemistry of each colour, the result may slightly vary.  
! We recommend to perform a test before launching a production! (+/- 10°C, +/- 5 sec).

## CARE AND WASHING RECOMMENDATIONS

Washing	Ironing	Tumble dry	Dry cleaning	Storage Shelf Life	Storage Temperature	Storage Conditions	Position
Hand wash or inside out in cold water	NO	NO	NO	Up to 2 years	Between 18°C and 26°C	Away from sunlight and dust	Vertical

- Wait 24 hours after the application before the first wash
- Respect the textile recommendations
- Do not bleach or use aggressive chemical agents

This document can be subject to variations. Updated versions are available on [www.siser.com](http://www.siser.com)  
For further information, please contact our sales office: [info@siser.it](mailto:info@siser.it)



Siser s.r.l.  
Viale della Tecnica, 18  
36100 Vicenza - Italy

Tel. +39 0444.287960  
Fax +39 0444.287959  
[info@siser.it](mailto:info@siser.it)  
[www.siser.com](http://www.siser.com)

r.e.a. vi 171856  
reg. imp. vi n° 14971  
c.s. € 103.300 i.v.  
p.iva 01591490246



Management System  
ISO 9001:2015  
ISO 14001:2015

